

Modellübersicht

Brennzellen | Kaminkassetten | Heizeinsätze | Kaminöfen

Welche
Feuerstätten
entsprechen den
neuen Grenzwerten
für Österreich nach

§ 15a B-VG?

(ab 1.1.2015)



SPARTHERM®
Feuerungstechnik

Stand 1|2015

Spalte	Anforderungen	Staub	CO	Wirkungsgrad in %			Nox	CnHm
				Einsatz	Ofen	Kachelofen		
Art. 15a (2015)	B-VG: Österreich	35 mg/MJ	1100 mg/MJ	80			150 mg/MJ	50 mg/MJ
	B-VG: Österreich (für Pelletöfen)	25 mg/MJ	500 mg/MJ	-	80	-	100 mg/MJ	30 mg/MJ

		Türhöhe	NWL in kW	Art. 15a
Mini	Mini R1V-4S	51,0	5,2	✓
	Mini R1V-4S <i>RLU</i>	51,0	5,2	✓
	Mini R1V-4S <i>NSHF</i>	51,0	6,2	✓
	Mini R1V-4S	57,0	5,0	✓
	Mini R1V-4S <i>RLU</i>	57,0	5,2	✓
	Mini R1V-4S <i>NSHF</i>	57,0	6,0	✓
	Mini R1Vh-4S	57,3	5,0	✓
	Mini R1Vh-4S <i>NSHF</i>	57,3	6,0	✓
	Mini Z1-8 kW-4S	51,0	8,0	✓
	Mini Z1-10 kW-4S <i>NSHF</i>	51,0	10,0	✓
	Mini Z1-8 kW-4S	57,0	8,0	✓
	Mini Z1-10 kW-4S <i>NSHF</i>	57,0	10,0	✓
	Mini Z1-4S <i>RLU</i>	51/57	7,0	✓*
	Mini Z1 H ₂ O-4S	51	7,0	✓
	Mini Z1 H ₂ O-4S <i>RLU</i>	51	7,0	✓
	Mini Z1 H ₂ O XL-4S	51	10,0	✓
	Mini Z1 H ₂ O XL-4S <i>RLU</i>	51	10,0	✓
	Mini Z1h H ₂ O XL-4S	51	10,0	✓
	Mini S-4S	51	7,0	✓
	Mini S-4S <i>RLU</i>	51	7,0	✓*
	Mini Sh-4S	51	7,0	✓
	Mini Sh-3S	51	7,0	✓
	Mini S-FDh-4S	51,3/57,3	6,0	✓*
	Mini S-FDh-3S	48,3	6,0	✓*
	Mini 2L-4S / 2R-4S	49,5/55,5	7,0	✓
	Mini 2LRh-4S	50/56	7,0	✓
Speedy	Speedy 1V-4S	51/57	9,0	✓
	Speedy 1V-4S <i>NSHF</i>	51/57	10,0	✓
	Speedy 1V-4S <i>RLU</i>	51/57	9,0	✓
	Speedy 1V-4S <i>Export</i>	51/57	14,5	✓*
	Speedy 1Vh-4S	51,3/57,3	9,0	✓
	Speedy 1Vh-4S <i>NSHF</i>	51,3/57,3	10,0	✓
	Speedy 1Vh-4S <i>Export</i>	51,3/57,3	14,5	✓*
	Speedy MR	51/57	9,0	✓
	Speedy MR	51/57	7,0	✓
	Speedy MRh	51/57	9,0	✓
	Speedy MRh	51/57	7,0	✓
	Speedy R	51/57	9,0	✓*
	Speedy R <i>NSHF</i>	51/57	10,0	✓
	Speedy Rh	51/57	9,0	✓*
	Speedy Rh <i>NSHF</i>	51/57	10,0	✓
	Speedy Ph	57	7,0	-
	Speedy MDRh	57	9,0	✓*
	Speedy RDRh	57	11,0	-
	Speedy M	51/57	8,0	✓
	Speedy M <i>NSHF</i>	51/57	9,0	✓
	Speedy Mh	51/57	8,0	✓
	Speedy Mh <i>NSHF</i>	51/57	9,0	✓

		Türhöhe	NWL in kW	Art. 15a
Speedy	Speedy K	51/57	9,0	✓*
	Speedy K <i>NSHF</i>	51/57	10,0	✓
	Speedy Kh	51/57	9,0	✓*
	Speedy Kh <i>NSHF</i>	51/57	10,0	✓
	Magic	57,3	12,0	✓
	Varia 1V-4S	51,0	7,0	✓
	Varia 1V-4S	51,0	11,0	-
	Varia 1V-4S <i>RLU</i>	51,0	11,0	-
	Varia 1V-4S <i>Export</i>	51,0	17,5	-
	Varia 1V-4S	57,0	7,0	✓
Varia	Varia 1V-4S	57,0	11,0	✓
	Varia 1V-4S <i>RLU</i>	57,0	11,0	✓
	Varia 1V-4S <i>Export</i>	57,0	17,5	✓*
	Varia 1V-4S <i>RLU</i>	51/57	7,0	✓
	Varia 1V H ₂ O-4S	51,0	8,0	✓
	Varia 1V H ₂ O-4S <i>Export</i>	51,0	11,0	✓
	Varia 1V H ₂ O XL-4S	51,0	9,0	✓
	Varia 1V H ₂ O XL-4S <i>Export</i>	51,0	12,0	✓
	Varia 1V H ₂ O XXL-4S	51,0	15,0	✓
	Varia 1V H ₂ O XXL-4S <i>Ex.</i>	51,0	22,0	✓
	Varia 1Vh-4S	45,3	7,0	✓
	Varia 1Vh-4S	45,3	11,0	-
	Varia 1Vh-4S	51,3	7,0	✓
	Varia 1Vh-4S	51,3	11,0	-
	Varia 1Vh-4S <i>Export</i>	51,3	17,5	-
	Varia 1Vh-4S	57,3	7,0	✓
	Varia 1Vh-4S	57,3	11,0	✓
	Varia 1Vh-4S <i>Export</i>	57,3	17,5	✓*
	Varia 1Vh H ₂ O-4S	51,3	9,0	✓
	Varia 1Vh H ₂ O-4S <i>Export</i>	51,3	11,0	✓
	Varia 1Vh H ₂ O-4S <i>XS RLU</i>	51,3	9,0	✓
	Varia 1Vh H ₂ O XL-4S	51,3	9,0	✓
	Varia 1Vh H ₂ O XL-4S <i>Ex.</i>	51,3	12,0	✓
	Varia 1Vh H ₂ O XL-4S <i>RLU</i>	51,3	14,4	-
	Varia 1Vh H ₂ O XXL-4S	51,3	15,0	✓
	Varia 1Vh H ₂ O XXL-4S <i>Ex.</i>	51,3	22,0	✓
	Varia 1Vh H ₂ O XXL-4S <i>RLU</i>	51,3	21,1	-
	Varia 1Vh-3S	44,3	7,0	✓
	Varia 1Vh-3S	44,3	11,0	-
	Varia 1Vh-3S	50,3	7,0	✓
	Varia 1Vh-3S	50,3	11,0	-
	Varia 1Vh-3S	56,3	7,0	✓
	Varia 1Vh-3S	56,3	11,0	✓
	Varia 1V-100h-4S	70,0	10,4	✓
	Varia 1V-100h-4S <i>Export</i>	70,0	17,0	✓
	Varia 1V-100h <i>Prestige</i>	70,0	10,4	✓
	Varia 1V-100h <i>Prest./Exp.</i>	70,0	17,0	✓
	Varia Sh-4S	62,3	11,0	✓

		Türhöhe	NWL in kW	Art. 15a
Varia	Varia Sh-3S	59,3	11,0	✓
	Varia SRh	69,0	11,0	✓*
	Varia AS-4S-2	36,6	7,0	✓
	Varia AS-4S-2 <i>NSHF</i>	36,6	11,0	✓
	Varia AS-4S-2 <i>Export</i>	36,6	11,0	✓
	Varia AS-4S-2 <i>RLU</i>	37,7	7,0	-
	Varia ASH-4S-2	37,0	7,0	✓
	Varia ASH-4S-2 <i>NSHF</i>	37,0	7,0	✓
	Varia ASH-4S-2 <i>Export</i>	37,0	11,0	✓
	Varia ASH-3S-2	37,0	7,0	✓
	Varia ASH-3S-2 <i>NSHF</i>	37,0	11,0	✓
	Varia ASH-3S-2 <i>Export</i>	37,0	11,0	✓
	Varia Ah-4S	43,0	10,4	✓
	Varia Ah H ₂ O-4S	43,8	10,4	✓
	Varia Ah H ₂ O-4S <i>Export</i>	43,8	14,0	✓
	Varia Ah-3S	43,0	10,4	✓
	Varia Ah-4S-2	43,0	9,0	-
	Varia Ah-3S-2	43,0	9,0	-
	Varia Bh-4S	52,4	10,4	✓*
	Varia Bh-4S	52,4	9,0	✓*
	Varia Bh-3S	49,3	10,4	✓*
	Varia Bh-120h-4S	52,3	15,0	✓*
	Varia Bh-120h-3S	49,3	15,0	✓*
	Varia M-60h-4S	52,4	7,0	✓*
	Varia M-60h <i>GET/DH</i>	51,4	8,0	✓
	Varia M-80h-4S	52,4	11,0	✓*
	Varia M-80h <i>GET/DH</i>	52	9,0	✓
	Varia M-100h-4S	52,4	11,0	✓*
	Varia M-100h <i>GET/DH</i>	52	10,4	✓
	Varia FD-4S	51/57	11,0	*
	Varia FD-4S <i>RLU</i>	51	11,0	-
	Varia FDh-4S	51,3/57,3	11,0	*
	Varia FDh-3S	50,3/56,3	11,0	*
	Varia AS-FD-4S-2	36,6	7,0	✓
	Varia AS-FD-4S-2 <i>NSHF</i>	37,7	7,0	✓
	Varia AS-FD-4S-2 <i>RLU</i>	37,7	7,0	✓
	Varia AS-FD-4S-2 <i>Export</i>	37,7	11,0	✓
	Varia AS-FDh-4S-2	37,0	7,0	✓
	Varia AS-FDh-4S-2 <i>NSHF</i>	37,0	11,0	✓
	Varia AS-FDh-4S-2 <i>Export</i>	37,0	11,0	✓
	Varia AS-FDh-3S-2	37,0	7,0	✓
	Varia AS-FDh-3S-2 <i>NSHF</i>	37,0	11,0	✓
	Varia AS-FDh-4S	43,8	10,4	✓
	Varia A-FDh-4S	43,8	10,4	✓
	Varia A-FDh H ₂ O-4S	43,8	10,4	✓
	Varia A-FDh H ₂ O-4S <i>Ex.</i>	43,8	15,0	✓
	Varia A-FDh-3S	42,8	10,4	✓
	Varia B-FDh-4S	52,3	11,0	✓*

Legende: ✓ erfüllt die Anforderungen | ✓* erfüllt nur mit AT-Aufsatz (Aufsatzaggregat S), Achtung: Abgasanschlusshöhe + 160 mm | * wird zur Zeit geprüft

Spalte	Anforderungen	Staub	CO	Wirkungsgrad in %			Nox	CnHm
				Einsatz	Ofen	Kachelofen		
Art. 15a (2015)	B-VG: Österreich	35 mg/MJ	1100 mg/MJ	80			150 mg/MJ	50 mg/MJ
	B-VG: Österreich (für Pelletöfen)	25 mg/MJ	500 mg/MJ	-	80	-	100 mg/MJ	30 mg/MJ

	Türhöhe	NWL in kW	Art. 15a
Varia B-FDh-3S	49,3	11,0	✓*
Varia 2L-55-4S	51,0	7,0	✓
Varia 2L-55h-4S	51,0	7,0	✓
Varia 2L-55h GET / DH	51,2	7,0	✓
Varia 2L-55h H ₂ O-4S	51,2	7,0	-
Varia 2L-55h H ₂ O-4S Ex.	51,2	12,0	-
Varia 2L	51,0	11,0	✓
Varia 2L	51,0	7,0	✓*
Varia 2L RLU	51,0	7,0	✓*
Varia 2L NSHF	51,0	12,0	✓
Varia 2L-4S RLU	51,0	11,0	✓
Varia 2Lh-4S	51,2/57,2	11,0	✓
Varia 2Lh-4S	51,2/57,2	7,0	✓*
Varia 2Lh-4S NSHF	51,2/57,2	12,0	✓
Varia 2Lh H ₂ O-4S	51,2	10,4	-
Varia 2Lh H ₂ O-4S	51,2	14,7	✓
Varia AS-2Lh-4S	37	7,0	✓
Varia 2L-80h-4S	51,2	10,4	✓
Varia 2L-80h-4S Export	51,2	16,0	-
Varia 2L-100h-4S	52,2	11,0	✓*
Varia 2R-55-4S	51	7,0	✓
Varia 2R-55h-4S	51	7,0	✓
Varia 2R-55h GET / DH	51,2	7,0	✓
Varia 2R-55h H ₂ O-4S	51,2	7,0	-
Varia 2R-55h H ₂ O-4S Ex.	51,2	12,0	-
Varia 2R	51,0	11,0	✓
Varia 2R	51,0	7,0	✓*
Varia 2R RLU	51,0	7,0	✓*
Varia 2R NSHF	51,0	12,0	✓
Varia 2R-4S RLU	51,0	11,0	✓
Varia 2Rh-4S	51,2/57,2	11,0	✓
Varia 2Rh-4S	51,2/57,2	7,0	✓*
Varia 2Rh-4S NSHF	51,2/57,2	12,0	✓
Varia 2Rh H ₂ O-4S	51,2	10,4	-
Varia 2Rh H ₂ O-4S	51,2	14,7	✓
Varia AS-2Rh-4S	37,0	7,0	✓
Varia 2R-80h-4S	51,2	10,4	✓
Varia 2R-80h-4S Export	51,2	16,0	-
Varia 2R-100h-4S	52,2	11,0	✓*
Varia 2LR-55h-4S	51,0	7,0	✓
Varia 2LRh	51,0	11,0	✓
Varia 2LRh	51,0	7,0	✓*
Varia 2LRh NSHF	51,0	12,0	✓
Varia 2RR-55h-4S	51,0	7,0	✓
Varia 2RRh	51,0	11,0	✓
Varia 2RRh	51,0	7,0	✓*
Varia 2RRh NSHF	51,0	12,0	✓
Varia C-45h	52,6	8,0	✓

	Türhöhe	NWL in kW	Art. 15a
Varia			
Varia Ch-4S	52,6	9,0	✓
Varia Eh-4S	51,0	11,0	✓*
Varia BEh-4S	51,2	11,0	-
Arte			
Arte 1Vh-4S	80,3	8,0	✓
Arte F-1V-4S	72,6	5,9	✓
Arte F 1V-4S NSHF	72,6	9,4	✓
Arte F 1V-4S Export	72,6	9,4	✓
Arte F 1Vh-4S	69,8	5,9	✓
Arte F 1Vh-4S NSHF	69,8	9,4	✓
Arte F 1Vh-4S Export	69,8	9,4	✓
Arte Bh-4S	80,3	11,0	✓*
Arte Bh-3S	79,3	11,0	✓*
Arte Xh-3S	66,0	11,0	✓*
Arte F-FD-4S	72,6	5,9	✓
Arte F-FD-4S NSHF	72,6	9,4	✓
Arte F-FD-4S Export	72,6	9,4	✓
Arte F-FDh-4S	69,8	5,9	✓
Arte F-FDh-4S NSHF	69,8	9,4	✓
Arte F-FDh-4S Export	69,8	9,4	✓
Arte X-FDh-3S	66,0	11,0	✓*
Arte U-50h	54,4	9,0	✓
Arte U-70h	54,4	11,0	✓*
Arte U-90h	54,4	13,0	✓*
Arte 3RL-60h	57,0	7,5	✓
Arte 3RL-80h	57,0	9,0	✓
Arte 3RL-100h	57,0	11,0	✓*
Arte BRh-4S	80,0	11,0	✓*
Kaminkassetten			
Kaminkassette klein	-	6,0	✓
Kaminkassette groß	-	8,0	✓
LK XS 500 D5	-	4,0	✓
LK XS 500 D5	-	4,6	✓
LK S 600 D5	-	4,9	✓
LK S 600 E5	-	4,9	✓
LK M 700 D6	-	5,9	✓
LK M 700 E7	-	6,9	✓
LK L 800 D8	-	7,9	✓
LK L 800 E10	-	9,9	✓
LK XL 900 D11	-	10,5	✓
LK XL 900 E14	-	14,0	-
Classic			
Nova E H ₂ O	45,0	14,0	✓
Nova F-Air	51/57	10,1	✓
Renova A H ₂ O	45,0	13,4	✓
Renova B-Air	51/57	8,8	✓
Renova C	59,4	8,5	✓
ambiente			
ambiente a1	-	6,3	✓
ambiente a1 RLU	-	6,3	✓
ambiente a2	-	6,3	✓
ambiente a2 RLU	-	6,3	✓

	Türhöhe	NWL in kW	Art. 15a
ambiente			
ambiente a3	-	6,3	✓
ambiente a3 RLU	-	6,3	✓
ambiente a4	-	6,3	✓
ambiente a4 H ₂ O	-	8,0	✓
ambiente a4 H ₂ O RLU	-	8,0	✓
ambiente a5	-	7,0	-
ambiente a7	-	5,9	✓
ambiente a8	-	5,9	✓
selection			
selection Stovo S	-	5,0	✓
selection Stovo M	-	5,0	✓
selection Stovo L	-	5,0	✓
selection Sino L	-	7,0	*
selection Sino City	-	5,0	✓
selection Moro	-	5,0	✓
selection Noto	-	7,0	✓
selection Senso S	-	7,0	✓
selection Senso S RLU	-	7,0	✓
selection Senso M H ₂ O	-	7,9	✓
selection Senso L	-	7,0	*
selection Passo XS	-	5,0	-
selection Passo XS RLU	-	5,0	-
selection Passo S	-	7,0	✓
selection Passo M	-	7,4	✓
selection Passo L	-	7,0	✓
selection Piko S	-	5,9	✓
selection Piko S RLU	-	5,9	✓
selection Piko M	-	5,9	✓
selection Piko M RLU	-	6,0	✓
selection Piko M + HF	-	5,9	✓
selection Piko L	-	5,9	✓
selection Piko L RLU	-	5,9	✓
selection Piko L + HF	-	5,9	✓
selection Piko H2O	-	7,9	✓
selection Cubo S	-	5,9	✓
selection Cubo S RLU	-	5,9	✓
selection Cubo M	-	5,9	✓
selection Cubo M RLU	-	6,0	✓
selection Cubo + HF	-	5,9	✓
selection Cubo L	-	5,9	✓
selection Cubo L RLU	-	5,9	✓
selection Cubo L + HF	-	5,9	✓
selection Piu	-	7,0	-
Mellino Pelletofen	-	8,0	✓



SPARTHERM Feuerungstechnik GmbH

Maschweg 38 · D-49324 Melle · Telefon +49 5422 94 41-0 · Fax +49 5422 94 41-14 · info@spartherm.com · www.spartherm.com